







COBRA CUFFS[®] SPECIFICATION SHEET

DIMENSIONS, FOLDED		FOLDABLE -EASY TO DEPLOY	
OVERALL LENGTH:	7.5 INCH		
OVERALL WIDTH:	1.5 INCH		
OVERALL DEPTH:	0.9 INCH		
STRAP WIDTH:	0.56 INCH		
STRAP OPENING DIAMETER:	7.5 INCH		
Resin Properties Test Method UNITS		COLOR CODE YOUR PRISONER	
Tear Strength	ASTM D-624	587 Pli	 <p style="text-align: center;">Blue Trainer</p>
Tensile Strength	ASTM D-412	2,390 psi	
Specific Gravity	ASTM D-792	0.94	
Compression Set	ASTM D-395	43%	
Hot air aging@302F	ASTM D-573	95%	
Double Loop Tensile Strength:		400+ lbs	
FEATURES		PRESS PICK-PROOF DOUBLE-LOCK	
<p>*Includes Double-Locking Clip; Helps Prevent Over-Tightening & Tampering -Superior Leverage</p> <p>*Compact Design / Weight (2 Oz)</p> <p>*Unique Rubber Based Polymer Resistant to stress cracking & brittleness. *5-7 Year Shelf Life*</p>		<p style="color: red; font-weight: bold;">Push Down to Lock</p> 	
		<p>STANDARD COLORS: BLACK, WHITE, GREEN, TAN</p>	
		<p>P.O. Box 16572 Asheville, NC 28816</p>	
PH (800) 525-9878	FAX (828) 785-4308	<p>Made in USA www.CobraCuffs.com</p>	
<p>PART # MS24D-250</p>		<p>MILSPEC PLASTICS</p>	

