







# COBRA CUFFS<sup>®</sup> SPECIFICATION SHEET

DIMENSIONS, FOLDED		FOLDABLE -EASY TO DEPLOY	
OVERALL LENGTH:	7.5 INCH		
OVERALL WIDTH:	1.5 INCH		
OVERALL DEPTH:	0.9 INCH		
STRAP WIDTH:	0.56 INCH		
STRAP OPENING DIAMETER:	7.5 INCH		
Resin Properties    Test Method    UNITS		COLOR CODE YOUR PRISONER	
Tear Strength	ASTM D-624	587 Pli	 <p style="text-align: center; margin-top: 5px;">Blue Trainer</p>
Tensile Strength	ASTM D-412	2,390 psi	
Specific Gravity	ASTM D-792	0.94	
Compression Set	ASTM D-395	43%	
Hot air aging@302F	ASTM D-573	95%	
Double Loop Tensile Strength: <b>400+ lbs</b>			
FEATURES		PRESS PICK-PROOF DOUBLE-LOCK	
*Includes Double-Locking Clip; Helps Prevent Over-Tightening & Tampering -Superior Leverage		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p style="color: red; font-weight: bold; margin-bottom: 5px;">Push Down to Lock</p>  </div> <div style="text-align: center;">  </div> </div>	
*Compact Design / Weight (2 Oz)			
*Unique Rubber Based Polymer Resistant to stress cracking & brittleness. <b>*5-7 Year Shelf Life*</b>			
<b>PART # MS24D-250</b>		STANDARD COLORS: BLACK, WHITE, GREEN, TAN	
<b>MILSPEC PLASTICS</b>		P.O. Box 16572 Asheville, NC 28816	
PH (800) 525-9878	FAX (828) 785-4308	Made in USA <a href="http://www.CobraCuffs.com" style="color: blue; text-decoration: underline;">www.CobraCuffs.com</a>	